

Product Data Sheet

GP LD CDM 2.1-25W E14 W FM FR

Order code	EAN	Packaging - SKU	
080411-LDCE1	4986149080411	Eco blister, 1 pc/SKU	1
Product			
Category		LED Lamps	- /
Series		VINTAGE CANDLE- FROSTED (FILAMENT)	
Selles		DECO	
Model		MINI CANDLE	
		FROSTED-FM	
Description		GP LD CDM E14 2.1-25W 220-240V FR FM CE1	
Description		GF ED CDM E 14 2.1-23W 220-240V FK FM CE 1	
General descriptio	on		1 20
Energy label		E	
Lamp shape		Candle	
Lamp base		E14	
Dimmable		No	
Mercury free		Yes	
Mercury content		0.0 mg	
Recycling		Yes	
			07:0
Electrical characteristics			97±3
Nominal wattage		2.1 W ±10%	
Rated wattage		2.1 W	
Equivalent incandescent lamp power		25 W	
Power factor		-	Spectral Distribution
Voltage		220-240 V	1.2
Operating frequency		50/60Hz	1.0-
Lamp current		25mA	
Weighted Energy Con	sumption	3 KWh / 1000 h	0.8- 5
			- U - U - U - U - U - U - U - U
Light technical characteristics			0.4
Light colour		WARM WHITE	
Colour temperature		2700 K ±270K	0.2
Colour rendering inde	x (Ra)	≥80	0.0
Colour consistency		<6 SDCM	Wavelength(nm)
Nominal luminous flux	(250 lm ±10%	
Rated luminous flux		250 lm	GP LED Lamps are designed for
Lumen maintenance f	actor at end of life	≥0.7	true direct replacement of standard
Warm-up time (60%)		Instant s	incandescent lamps.
Starting time		<0.5s s	 Compatible shapes and sizes of GLS
			 Very low energy consumption
Lifespan			Extremely long life
Nominal life time		15000 h	 Emit a warm white or cold white light
Rated lamp life time		15000 h	for different ambience
Switching cycles		50000	 Instant start with full light output
			 Available in most common lamp bases
Product dimensions		for household use	
Overall length (L)		97 mm ±1 mm	• No UV
Diameter (D)		35 mm ±1 mm	
			Applications
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications
Warranty		12 months from ex-factory date	General illumination
-		· · · · ·	Can be used everywhere at home
			Use outdoors only in enclosed and
			ventilated luminaires

www.gp-lighting.com