

Product Data Sheet

GP LD CLS60 10-100W E27 W FM CL

Order code	EAN	Packaging - SKU	
086536-LDCE1	4895149086536	Eco blister, 1 pc/SKU	
			THE
Product			
Category		LED Lamps	
Series		VINTAGE CLASSIC- CLEAR (FILAMENT)	
Model		CLASSIC FILAMENTCLEAR	ATT.
Description		GP LD CLS60 E27 10-100W 220-240V CL FM	
General description	n		
Energy label		D	
_amp shape		Classic A60	
Lamp base		E27	60
Dimmable		No	
Mercury free		Yes	
Mercury content		0.0 mg	104
Recycling		Yes	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Electrical characte	eristics		
Nominal wattage		10 W ±10%	
Rated wattage		10 W	
Equivalent incandesce	ent lamp power	100 W	
Power factor		>0.5	Spectral Distribution
Voltage Operating frequency Lamp current		220-240V	
		50/60Hz	Spectrum 1.0=31.115mW/nm 1.2
		41-46mA	1.0-
Weighted Energy Consumption		10 KWh / 1000 h	0.8-
			0.6
Light technical characteristics			0.4-
Light colour		WARM WHITE	0.2-
Colour temperature		2700 K ±150K	0.0350 513 675 838 1000 Wavelength (nm)
Colour rendering inde	(Ra)	≥80	Wavelength (nm)
Colour consistency		<6 SDCM	
Nominal luminous flux		1521 lm ±10%	
Rated luminous flux		1521 lm	GP LED Lamps are designed for
Lumen maintenance fa	actor at end of life	≥0.8	true direct replacement of standard
Warm-up time (60%)		<0.5 s	incandescent lamps.
Starting time		<0.5 s	Compatible shapes and sizes of GLS
·			Very low energy consumption
Lifespan			Extremely long life
Nominal life time		15000 h	Emit a warm white or cold white light
Rated lamp life time		15000 h	for different ambience
Switching cycles		20000	Instant start with full light output
			Available in most common lamp bases
Product dimensions			for household use
Overall length (L)		104 mm ±1 mm	• No UV
Diameter (D)		60 mm ±1 mm	
			Applications
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications
Warranty		12 months from ex-factory date	General illumination
			Can be used everywhere at home
			Use outdoors only in enclosed and
			ventilated luminaires

www.gp-lighting.com