

## **Product Data Sheet**

## GP LD CDM 4-40W E14 W FM CL

Order code	EAN	Packaging - SKU	
778128-LDCE1	4986149078128	Eco blister, 1 pc/SKU	
Product			
Category		LED Lamps	
Series		VINTAGE CANDLE- CLEAR (FILAMENT)	
		DECO	\
Model		MINI CANDLE	( .1_1. )
		CLEAR-FM	
Description		GP LD CDM E14 4-40W 220-240V CL FM CE1	
			U. 100
General description	on		E-31
Energy label		E	8
Lamp shape		Candle	E-23
Lamp base		E14	
Dimmable		No	
Mercury free		Yes	
Mercury content		0.0 mg	
Recycling		Yes	
			97
Electrical characte	eristics		- 01
Nominal wattage		4 W ±10%	
Rated wattage		4 W	
Equivalent incandescent lamp power		40 W	
Power factor		-	Spectral Distribution
Voltage		220-240 V	1.21
Operating frequency		50/60Hz	1.0-
Lamp current		42 mA	
Weighted Energy Consumption		4 KWh / 1000 h	0.8-
0 0,			- 0.6-
Light technical ch	aracteristics		
Light colour		WARM WHITE	0.4
Colour temperature		2700 K ±270K	0.2-
Colour rendering index (Ra)		≥80	0.0380 500 600 700 800
Colour consistency		<6 SDCM	380 500 600 700 800 Wavelength(nm)
Nominal luminous flux		470 lm ±10%	
Rated luminous flux		470 lm	GP LED Lamps are designed for
Lumen maintenance factor at end of life		≥0.7	true direct replacement of standard
Warm-up time (60%)		Instant s	incandescent lamps.
Starting time		<0.5s s	Compatible shapes and sizes of GLS
, , , , ,			Very low energy consumption
Lifespan			Extremely long life
Nominal life time		15000 h	Emit a warm white or cold white light
Rated lamp life time		15000 h	for different ambience
Switching cycles		50000	Instant start with full light output
			Available in most common lamp bases
Product dimensions			for household use
Overall length (L)		97 mm ±1 mm	• No UV
Diameter (D)		35 mm ±1 mm	
\-/-/		'	Applications
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications
Warranty		12 months from ex-factory date	General illumination
·· · · · · · · · · · · · · · · · · · ·			Can be used everywhere at home
			Use outdoors only in enclosed and
			ventilated luminaires

## www.gp-lighting.com