

Product Data Sheet

GP LD DIM CLS60 4.2-40W E27 W FM CL

Order code	EAN	Packaging - SKU		
778210-LDCE1	4986149078210	Eco blister, 1 pc/SKU		
Product				
Category		LED Lamps		
Series		VINTAGE CLASSIC- CLEAR (FILAMENT)		
Model		HI-BRIGHTNESS CLASSIC		
		CLEAR-FM DIMMABLE		
Description		GP LD CLS60 E27 4.2-40W 220-240V CL FM DIN CE1		
General descriptio	n			
Energy label		E		
Lamp shape		Classic A60		
Lamp base		E27		
Dimmable		Yes	104	
Mercury free		Yes		
Mercury content		0.0 mg	40000	
Recycling		Yes		
Electrical characte	ristics		THE LEWIS CO.	
Nominal wattage		4.2 W ±10%		
Rated wattage		4.2 W	7	
Equivalent incandescent lamp power		40 W		
Power factor		>0.5	Spectral Distribution	
Voltage		220-240 V	1.21	
Operating frequency		50Hz	1.0-	
Lamp current		25 mA		
Weighted Energy Consumption		5 KWh / 1000 h	0.8-	
			89.0 c t t t t t t t t t t t t t t t t t t	
Light technical characteristics			0.4-	
Light colour		WARM WHITE	0.2	
Colour temperature	(5.)	2700 K ±270K	- ""	
Colour rendering index	((Ka)	≥80 <6 SDCM	0.0. 380 500 600 700 800 Wavelength (nm)	
Colour consistency			marezengen (im)	
Nominal luminous flux Rated luminous flux		470 lm ±10% 470 lm	GP LED Lamps are designed for	
Lumen maintenance factor at end of life		≥0.7	true direct replacement of standard	
Warm-up time (60%)		Instant	incandescent lamps.	
Starting time		<0.5s	Compatible shapes and sizes of GLS	
Canada anno		10.00	Very low energy consumption	
Lifespan			Extremely long life	
		15000 h	Emit a warm white or cold white light	
·			for different ambience	
Nominal life time		15000 h	for different ambience	
Nominal life time Rated lamp life time		15000 h 50000	Instant start with full light output	
Nominal life time				
Nominal life time Rated lamp life time	ns		Instant start with full light output	
Nominal life time Rated lamp life time Switching cycles Product dimension	ıs		Instant start with full light output Available in most common lamp bases	
Nominal life time Rated lamp life time Switching cycles Product dimensior Overall length (L)	ıs	50000	Instant start with full light output Available in most common lamp bases for household use	
Nominal life time Rated lamp life time Switching cycles Product dimensior Overall length (L)	IS	50000 104 mm ±1 mm	Instant start with full light output Available in most common lamp bases for household use	
Nominal life time Rated lamp life time Switching cycles Product dimensior Overall length (L) Diameter (D)	1S	50000 104 mm ±1 mm	Instant start with full light output Available in most common lamp bases for household use No UV	
Nominal life time Rated lamp life time Switching cycles Product dimensior Overall length (L)	ls.	50000 104 mm ±1 mm 60 mm ±1 mm	Instant start with full light output Available in most common lamp bases for household use No UV Applications	
Nominal life time Rated lamp life time Switching cycles Product dimensior Overall length (L) Diameter (D) Product Compliance Warranty		50000 104 mm ±1 mm 60 mm ±1 mm CE, ERP, ROHS, REACH	Instant start with full light output Available in most common lamp bases for household use No UV Applications Domestic and commercial applications	
Nominal life time Rated lamp life time Switching cycles Product dimensior Overall length (L) Diameter (D) Product Compliance Warranty		50000 104 mm ±1 mm 60 mm ±1 mm CE, ERP, ROHS, REACH 12 months from ex-factory date	Instant start with full light output Available in most common lamp bases for household use No UV Applications Domestic and commercial applications General illumination	

www.gp-lighting.com